

TechCool

Industry Specifications

- TMC RP 329
- Cummins CES14603
- Navistar
- ASTM D-6210
- Caterpillar
- Freightliner 48-22880
- ASTM D-4985
- Detroit Diesel 7SE298
- Volvo GM
- ASTM D-3306
- John Deere 8650-5
- PACCAR
- SAE 1941
- Case Corp. MS1710
- MACK
- GM 1825
- Ford New Holland 9-86
- EMD M.I. 1748E
- GM 1899
- Thermo-King
- Waukesha 4-1974D
- CID A-A 52624A

Fully Formulated Heavy Duty Coolant

Product Description

TechCool Fully Formulated Engine Coolant is designed for use in all heavy duty cooling system applications. It is manufactured using a Borate/Nitrite chemical inhibitor system. The low silicate formula, contains a full charge of Nitrite (1200ppm) and is compatible with SCA chemical filters. Borate/Nitrite formulated antifreezes are recommended for use in Caterpillar, Detroit Diesel, Cummins and other heavy duty diesel engines.

Product Specifications

Color: Green, Fuchsia or Clear (Optional)

Freeze Point: -34F

Nitrite: 1,200 ppm

Technical Contact Information

Antifreeze Technology Systems

1 Seasons Lane, Londonderry, NH 03053
Tel: 603-432-4444 | FAX: 603-432-4746
atsnh@aol.com